



RoHS

IP65

IK10+

RAL



MORO SM

L80 B10 > 100 000h | SDCM 3 | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
MORO SM XS 10	10W	1226 Lm	123 lm/W	380 x 150 x 65 mm	MSXS10
MORO SM XS 15	13W	1548 Lm	119 lm/W	380 x 150 x 65 mm	MSXS15
MORO SM S 15	14W	1685 Lm	120 lm/W	660 x 150 x 65 mm	MSMS15
MORO SM S 25	19W	2334 Lm	123 lm/W	660 x 150 x 65 mm	MSMS25
MORO SM S 30	22W	2899 Lm	132 lm/W	660 x 150 x 65 mm	MSMS30
MORO SM M 25	20W	2528 Lm	126 lm/W	940 x 150 x 65 mm	MSMM25
MORO SM M 35	28W	3502 Lm	125 lm/W	940 x 150 x 65 mm	MSMM35
MORO SM M 40	33W	4214 Lm	128 lm/W	940 x 150 x 65 mm	MSMM40
MORO SM L 30	25W	3113 Lm	125 lm/W	1220 x 150 x 65 mm	MSML30
MORO SM L 45	37W	4668 Lm	126 lm/W	1220 x 150 x 65 mm	MSML45
MORO SM L 55	43W	5619 Lm	131 lm/W	1220 x 150 x 65 mm	MSML55
MORO SM XL 40	31W	3891 Lm	126 lm/W	1500 x 150 x 65 mm	MSXL40
MORO SM XL 55	41W	5295 Lm	129 lm/W	1500 x 150 x 65 mm	MSXL55
MORO SM XL 60	46W	5805 Lm	126 lm/W	1500 x 150 x 65 mm	MSXL60
MORO SM XL 70	54W	7023 Lm	130 lm/W	1500 x 150 x 65 mm	MSXL70

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - zinc-plated steel; standard colour - white

DIFFUSER - opal polycarbonate

INFO - UV stable, vandal resistant, frame with stainless-steel security screws

INSTALLATION

On the ceiling (security bit to be ordered separately)

ACCESSORIES

Security screw drill bit for 2-hole security fixings

CODE

MORO-BIT

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

Corridor function (never off) COR

Corridor function 1min (switch off after 1 min.) COR1

Corridor function 30min (switch off after 30 min.) COR30

CASING COLOUR

Grey GR

Black BL

White WH

Custom RAL

EMERGENCY MODULE

3 hr EM

ADD-ONS

Microwave sensor MW

Order code example: **MSMS30-4K-DL-WH-EM**