



GARDA CR

L70 B10 > 50 000h | SDCM 3 | LLMF 84% | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
GARDA CR S 15	11W	1510 Lm	137 lm/W	Ø 155 x 40 mm	GCRS15
GARDA CR S 20	16W	2090 Lm	131 lm/W	Ø 155 x 40 mm	GCRS20
GARDA CR M 25	17W	2460 Lm	145 lm/W	Ø 225 x 40 mm	GCRM25
GARDA CR M 30	22W	3020 Lm	137 lm/W	Ø 225 x 40 mm	GCRM30
GARDA CR M 35	26W	3590 Lm	138 lm/W	Ø 225 x 40 mm	GCRM35

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - powder painted aluminum profile; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate

INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard ceiling

Surface mounted

Suspension

ACCESSORIES

	INFO	CODE
Surface mounting housing*	Ø 160 x 75 mm	GCRS-SMH160
	Ø 228 x 75 mm	GCRM-SMH228
Suspension set*	Central electrical suspension 3x	GCRM-SUSPS

*Any RAL colour option available. Order example: **GCRS-SMHO-GR**



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

EMERGENCY MODULE*

3 hr EM

*Available in GARDA CR M on request

Order code example: **GCRS20-4K-ST-BL**