



TOVEL

L80 B10 > 60 000h | SDCM 3 | CRI 80-95+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
TOVEL 20	13W	1924 Lm	148 lm/W	226 x 107 x 248 mm	TOVE20
TOVEL 25	20W	2613 Lm	131 lm/W	226 x 107 x 248 mm	TOVE25
TOVEL 35	27W	3518 Lm	130 lm/W	226 x 107 x 248 mm	TOVE35
TOVEL 45	35W	4414 Lm	126 lm/W	226 x 107 x 248 mm	TOVE45
TOVEL 50	42W	5014 Lm	119 lm/W	226 x 107 x 248 mm	TOVE50
TOVEL 55	47W	5606 Lm	119 lm/W	226 x 107 x 248 mm	TOVE55

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - aluminium;
standard colour - white

DIFFUSER - tempered glass

REFLECTOR - faceted aluminium,
60° light beam angle

INSTALLATION

In 3-phase track

ORDER CODE

COLOUR TEMPERATURE	
2000K Meat*	2KM
2500K Bread*	2.5KB
2700K Natural***	2.7KN
3100K Meat&White*	3.1KMW
3000K	3K
3000K Vegetables**	3KV
3000K Natural***	3KN
3100K Fashion&White**	3.2KFW
3200K Fashion**	3.2KF
4000K	4K
4000K Natural***	4KN

DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Grey	GR
Black	BL
White	WH
Custom	RAL
CRI	
80	C80
90	C90
95	C95



*Only available for CRI 80
** Only available for CRI 90
*** Only available for CRI 95

Order code example: **TOVE20-4K-DL-GR-C80**