



ORBIS

L80 B10 > 54 000h | SDCM 3 | LLMF 84% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
ORBIS 20	17W	2140 Lm	126 lm/W	Ø 400 x 110 mm	ORBI20
ORBIS 30	25W	3130 Lm	125 lm/W	Ø 400 x 110 mm	ORBI30

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - polycarbonate

DIFFUSER - OPQ-Opal/Polycarbonate with UV stabilization

INSTALLATION

Surface mounted

Wall mounted

ACCESSORIES

	INFO	CODE
Vandal Proof	Screw Set	ORBI-SCREWS
	Special Screwdriver	ORBI-SDRIVE



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

White WH

Grey GR

EMERGENCY MODULE

3 hr EM

ADD-ONS

Motion Sensor MS

CRI

≥ 90 C90

Order code example: **ORBI20-4K-ST-GR-MS**