



VACCA

L80 B10 > 60 000h | SDCM 3 | CRI 80-95+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
VACCA 20	14W	1924 Lm	137 lm/W	236 x 146 x 107 mm	VCCA20
VACCA 25	20W	2613 Lm	131 lm/W	236 x 146 x 107 mm	VCCA25
VACCA 35	27W	3518 Lm	130 lm/W	236 x 146 x 107 mm	VCCA35
VACCA 45	35W	4414 Lm	126 lm/W	236 x 146 x 107 mm	VCCA45
VACCA 50	42W	5014 Lm	119 lm/W	236 x 146 x 107 mm	VCCA50
VACCA 55	47W	5606 Lm	119 lm/W	236 x 146 x 107 mm	VCCA55

*Values are given for colour temperature of 4000K, CRI 80 and may variate for other options

MATERIALS

CASING - aluminium;
standard colour - white

DIFFUSER - tempered glass

REFLECTOR - faceted aluminium,
60° light beam angle, tilting 90°

INSTALLATION

In ceilings with cut-out openings
(mounting brackets included)

ORDER CODE

COLOUR TEMPERATURE

2000K Meat*	2KM
2500K Bread*	2.5KB
2700K Natural***	2.7KN
3100K Meat&White*	3.1KMW
3000K	3K
3000K Vegetables**	3KV
3000K Natural***	3KN
3100K Fashion&White**	3.2KFW
3200K Fashion**	3.2KF
4000K	4K
4000K Natural***	4KN

DRIVER TYPE

Standard	ST
Dimming - DALI	DL

CASING COLOUR

Grey	GR
Black	BL
White	WH
Custom	RAL

CRI

≥ 80	C80
≥ 90	C90
≥ 95	C95



*Only available for CRI 80
** Only available for CRI 90
*** Only available for CRI 95

Order code example: **VCCA20-4K-DL-GR-C80**