

SOLIS P

L80 B10 > 54 000h | SDCM 3 | LLMF 86% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOLIS P M 15	10W	1290 Lm	129 lm/W	595 x 295 x 70 mm	SOPM15
SOLIS P M 25	17W	2260 Lm	133 lm/W	595 x 295 x 70 mm	SOPM25
SOLIS P L 30	18W	2830 Lm	157 lm/W	595 x 595 x 70 mm	SOPL30
SOLIS P L 45	31W	4710 Lm	152 lm/W	595 x 595 x 70 mm	SOPL45
SOLIS P XL 30	18W	2720 Lm	151 lm/W	1195 x 295 x 70 mm	SPXL30
SOLIS P XL 45	31W	4540 Lm	146 lm/W	1195 x 295 x 70 mm	SPXL45
SOLIS P XXL 55	34W	5500 Lm	162 lm/W	1195 x 595 x 70 mm	SXXL55
SOLIS P XXL 90	60W	9170 Lm	153 lm/W	1195 x 595 x 70 mm	SXXL90

*Values are given for colour temperature of 4000K, HEX diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted steel; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA



INSTALLATION

Recessed into plaster-cardboard ceiling

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Micro-prismatic	HEX
Opal	OPQ

CASING COLOUR	
White	WH
Grey	GR
Black	BL
Custom	RAL
EMERGENCY MODULE	
3 hr	EM
ADD-ONS*	
Motion Sensor	MS
CRI	
≥ 90	C90
THROUGH WIRING*	
5-phase through wiring	TW5



*Available on request

Order code example: **SOPL30-4K-DL-HEX-WH**