



REBUS

L80 B10 > 100 000h | SDCM 3 | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
REBUS S L1	22W	3796 Lm	173 lm/W	1132 x 45 x 65 mm	REBSL1
REBUS S L2	32W	5260 Lm	164 lm/W	1132 x 45 x 65 mm	REBSL2
REBUS S L3	30W	5523 Lm	184 lm/W	1132 x 45 x 65 mm	REBSL3
REBUS S L4	36W	6567 Lm	182 lm/W	1132 x 45 x 65 mm	REBSL4
REBUS S L5	42W	7554 Lm	180 lm/W	1132 x 45 x 65 mm	REBSL5
REBUS M L1	27W	4746 Lm	176 lm/W	1413 x 45 x 65 mm	REBML1
REBUS M L2	39W	6575 Lm	169 lm/W	1413 x 45 x 65 mm	REBML2
REBUS M L3	37W	6904 Lm	187 lm/W	1413 x 45 x 65 mm	REBML3
REBUS M L4	44W	8209 Lm	187 lm/W	1413 x 45 x 65 mm	REBML4
REBUS M L5	52W	9442 Lm	182 lm/W	1413 x 45 x 65 mm	REBML5
REBUS L L1	52W	9491 Lm	183 lm/W	2818 x 45 x 65 mm	REBLL1
REBUS L L2	75W	13150 Lm	175 lm/W	2818 x 45 x 65 mm	REBLL2
REBUS L L3	73W	13808 Lm	189 lm/W	2818 x 45 x 65 mm	REBLL3
REBUS L L4	87W	16418 Lm	189 lm/W	2818 x 45 x 65 mm	REBLL4
REBUS L L5	102W	18884 Lm	185 lm/W	2818 x 45 x 65 mm	REBLL5

*Values are given for colour temperature of 4000K, 75° standard beam angle, CRI 80 and may vary for other options



MATERIALS

CASING - steel; standard colour - white

OPTICAL SYSTEM - lenses

INSTALLATION

Suspended (suspension brackets and I-joint kit included with each luminaire)

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
OPTICS WITH BEAM ANGLES	
30°	30
40x 75°	40x75
75° standard	75
75° wide	75W
90° wide	90W
100° diffused	100D
Asymmetric beam light direction - left	AS-L
Asymmetric beam light direction - right	AS-R
Double asymmetric beam	DAS
CASING COLOUR	
Grey	GR
Black	BL
White	WH
Custom	RAL
EMERGENCY MODULE	
3 hr	EM
CRI	
≥ 90	C90

Order code example: **REBSL1-4K-DL-75W-GR**

FIXINGS

	INFO	CODE
5-pole socket	Power supply socket 1602/VCB-M-5 5x1.5-2.5mm ² , 1pcs	REBU-5SOCK
CAP cable	Cable 3x0.75mm ² for suspended luminaire up to 2.0 meters, transparent	ZLISS-NC-CABL
	Cable and suspension wire clip set, 4pcs. For cable diameter up to 6,3mm and wire diameter 1mm	ZLISS-NC-CCLIP
Blank part Kit	Blank part kit for connecting luminaires in-line 1132mm long, 1pcs*	REBU-CNN1134
	Blank part kit for connecting luminaires in-line 1413mm long, 1pcs*	REBU-CNN1415
	Blank part kit for connecting luminaires in-line 2818mm long, 1pcs*	REBU-CNN2820
End cap	End cap kit for luminaires, 1pcs (extra)*	REBU-ENDCAP
Suspension Kit	Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 3x1x1.5mm ² , light grey/ white/ black*	ZLISS-NC-SUSP-SQ3
	Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 5x1x1.5mm ² , light grey/ white/ black*	ZLISS-NC-SUSP-SQ5
	Suspension wire set "1" type, 1.5m adjustable, 1pcs	ZLISS-NC-SUSP-W

*Any RAL colour option available. Order example: **REBU-ENDCAP-GR**

