



RoHS

IP20

RAL



**TENNO**

L80 B10 > 60 000h | SDCM 3 | CRI 80-95+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
TENNO 20	14W	1901 Lm	136 lm/W	175 x 175 x 119 mm	TENN20
TENNO 25	19W	2583 Lm	136 lm/W	175 x 175 x 119 mm	TENN25
TENNO 35	27W	3478 Lm	129 lm/W	175 x 175 x 119 mm	TENN35
TENNO 40	27W	3803 Lm	141 lm/W	350 x 175 x 119 mm	TENN40
TENNO 50	37W	5167 Lm	140 lm/W	350 x 175 x 119 mm	TENN50
TENNO 70	53W	6956 Lm	131 lm/W	350 x 175 x 119 mm	TENN70

\*Values are given for colour temperature of 4000K, beam angle 40°, CRI 80 and may vary for other

### MATERIALS

CASING - aluminium;  
standard colour - white

DIFFUSER - clear PMMA

REFLECTOR - faceted aluminium

### INSTALLATION

In ceilings with cut-out openings  
(mounting brackets included)

### ORDER CODE

#### COLOUR TEMPERATURE

2000K Meat*	2KM
2500K Bread*	2.5KB
2700K Natural***	2.7KN
3100K Meat&White*	3.1KMW
3000K	3K
3000K Vegetables**	3KV
3000K Natural***	3KN
3100K Fashion&White**	3.2KFW
3200K Fashion**	3.2KF
4000K	4K
4000K Natural***	4KN

#### DRIVER TYPE

Standard	ST
Dimming - DALI	DL

#### CASING COLOUR

Grey	GR
Black	BL
White	WH
Custom	RAL

#### BEAM ANGLE

24°	24
40°	40

#### CRI

80	C80
90	C90
95	C95

\*Only available for CRI 80  
\*\* Only available for CRI 90  
\*\*\* Only available for CRI 95

Order code example: **TENN20-4K-DL-WH-40-C80**

