



CITTA I

L80 B10 > 100 000h | SDCM 3 | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
CITTA I 15	10W	1460 Lm	146 lm/W	600 x 80 x 62 mm	CITI15
CITTA I 20	11W	1791 Lm	163 lm/W	600 x 80 x 62 mm	CITI20
CITTA I 22	14W	2111 Lm	151 lm/W	600 x 80 x 62 mm	CITI22
CITTA I 25	16W	2433 Lm	152 lm/W	600 x 80 x 62 mm	CITI25
CITTA I 30	18W	2920 Lm	162 lm/W	600 x 80 x 62 mm	CITI30
CITTA I 35	22W	3583 Lm	163 lm/W	600 x 80 x 62 mm	CITI35
CITTA I 40	26W	4223 Lm	162 lm/W	600 x 80 x 62 mm	CITI40
CITTA I 50	31W	4867 Lm	157 lm/W	600 x 80 x 62 mm	CITI50

*Values are given for colour temperature of 4000K/WGC and may vary for other options

MATERIALS

CASING - steel; standard colour - white

DIFFUSER - double parabolic reflector with lenses, low glare

INSTALLATION

Recessed (in ceilings with cut-out openings. Push-in terminal, 3x2x2.5mm²)

ORDER CODE

COLOUR TEMPERATURE

3000K	3K
4000K	4K

DRIVER TYPE

Standard	ST
Dimming - DALI	DL
Slave luminaire with integrated EAIR type driver	EAIRB
Integrated wireless control unit and driver via Bluetooth	BLT
Corridor function (never off)	COR
Corridor function 1min (switch off after 1 min.)	COR1
Corridor function 30min (switch off after 30 min.)	COR30

REFLECTOR



White gloss	WGC
Black gloss	BGC
White matt	WMC
Black matt	BMC
Metallic mirror finish	MGC
Metallic matt	MMC
MGC asymm. with WH shade	WAC
MGC asymm. with BL shade	BAC

CASING COLOUR

White	WH
Grey	GR
Black	BL
Custom	RAL

EMERGENCY MODULE

3 hr	EM
------	----



Order code example: **CITI20-4K-ST-WGC-WH-EM**