



L80 B10 > 100 000h | SDCM 3 | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
MORO XS 10	10W	1226 Lm	123 lm/W	410 x 180 x 65 mm	MRXS10
MORO XS 15	13W	1548 Lm	119 lm/W	410 x 180 x 65 mm	MRXS15
MORO S 15	14W	1685 Lm	120 lm/W	690 x 180 x 65 mm	MROS15
MORO S 25	19W	2334 Lm	123 lm/W	690 x 180 x 65 mm	MROS25
MORO S 30	22W	2899 Lm	132 lm/W	690 x 180 x 65 mm	MROS30
MORO M 25	20W	2528 Lm	126 lm/W	970 x 180 x 65 mm	MROM25
MORO M 35	28W	3502 Lm	125 lm/W	970 x 180 x 65 mm	MROM35
MORO M 40	33W	4214 Lm	128 lm/W	970 x 180 x 65 mm	MROM40
MORO L 30	25W	3113 Lm	125 lm/W	1250 x 180 x 65 mm	MROL30
MORO L 45	37W	4668 Lm	126 lm/W	1250 x 180 x 65 mm	MROL45
MORO L 55	43W	5619 Lm	131 lm/W	1250 x 180 x 65 mm	MROL55
MORO XL 40	31W	3891 Lm	126 lm/W	1530 x 180 x 65 mm	MRXL40
MORO XL 55	41W	5295 Lm	129 lm/W	1530 x 180 x 65 mm	MRXL55
MORO XL 60	46W	5805 Lm	126 lm/W	1530 x 180 x 65 mm	MRXL60
MORO XL 70	54W	7023 Lm	130 lm/W	1530 x 180 x 65 mm	MRXL70

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - zinc-plated steel; standard colour - white

DIFFUSER - opal polycarbonate

INFO - UV stable, vandal resistant, frame with stainless-steel security screws

INSTALLATION

In ceilings or walls with cut-out openings (mounting brackets included)

ACCESSORIES

	CODE
Security screw drill bit for 2-hole security fixings	MORO-BIT

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K

DRIVERTYPE	
Standard	ST
Dimming - DALI	DL
Corridor function (never off)	COR
Corridor function 1min (switch off after 1 min.)	COR1
Corridor function 30min (switch off after 30 min.)	COR30
CASING COLOUR	
Grey	GR
Black	BL
White	WH
Custom	RAL
EMERGENCY MODULE	
3 hr	EM
ADD-ONS	
Microwave sensor	MW

Order code example: **MROS30-4K-DL-WH-EM**

