

SOLIS

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	IP RATING	ORDER REFERENCE
SOLIS L 40 (Recessed)	30W	3680 Lm	123 lm/W	595 x 595 x 47 mm	IP44	SOLL40
SOLIS L 40 SP (Suspended)	30W	3680 Lm	123 lm/W	596 x 596 x 60 mm	IP40	SLSP40
SOLIS L 40 SM (Surface Mounted)	30W	3680 Lm	123 lm/W	623 x 623 x 60 mm	IP40	SLSM40
SOLIS L 40 PB (Plaster-in)	30W	3680 Lm	123 lm/W	621 x 621 x 57 mm	IP40/IP20	SLPI40
SOLIS XL 40 (Recessed)	30W	3760 Lm	125 lm/W	1196 x 296 x 47 mm	IP44	SOXL40
SOLIS XL 40 SP (Suspended)	30W	3760 Lm	125 lm/W	1196 x 296 x 60 mm	IP40	SXSP40
SOLIS XL 40 SM (Surface Mounted)	30W	3760 Lm	125 lm/W	1225 x 300 x 60 mm	IP40	SXSM40
SOLIS XL 40 PB (Plaster-in)	30W	3760 Lm	125 lm/W	1245 x 310 x 57 mm	IP40/IP20	SXPI40

*Values are given for 4000K colour temperature and may vary for other options

MATERIALS

CASING - electrostatically painted steel; standard colour - white

DIFFUSER - microprismatic



INSTALLATION

Suspended

Surface mounted

Recessed into the modular ceiling

Recessed into plaster-cardboard ceiling (600x600 version only)



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM

Order code example: **SOLL40-4K-DL-WH-EM**