



## PISTON SM

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
PISTON SM 15	15W	1470 Lm	98 lm/W	Ø 80 x 200 mm	PISM15
PISTON SM 20	21W	2030 Lm	97 lm/W	Ø 80 x 200 mm	PISM20
PISTON SM 25	29W	2640 Lm	91 lm/W	Ø 80 x 200 mm	PISM25

\*Values are given for 4000K, 50° beam angle, IP20 and may vary for other options

### MATERIALS

CASING - electrostatically painted aluminium;  
standard colour - anthracite grey

DIFFUSER - transparent tempered glass

### INSTALLATION

Ceiling mounted

### ORDER CODE

#### COLOUR TEMPERATURE

3000K	3K
4000K	4K

#### DRIVERTYPE

Standard	ST
Dimming - DALI	DL

#### CASING COLOUR

Grey	GR
White	WH
Black	BL
Custom	RAL

#### BEAM ANGLE

30°	30
50°	50
70°	70

#### IP RATING

IP20	IP20
IP44	IP44



Order code example: **PISM15-4K-ST-BL-50-IP20**