



## LITHIUM LITE SM

L80 B10 > 72 000h | SDCM 3 | LLMF 86% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
LITHIUM LITE SM 10	10W	1160 Lm	116 lm/W	Ø 228 x 180 mm	LISM10
LITHIUM LITE SM 15	15W	1590 Lm	106 lm/W	Ø 228 x 180 mm	LISM15
LITHIUM LITE SM 20	19W	2030 Lm	107 lm/W	Ø 228 x 180 mm	LISM20
LITHIUM LITE SM 30	28W	2750 Lm	98 lm/W	Ø 228 x 180 mm	LISM30

\*Values are given for 4000K colour temperature and may vary for other options

### MATERIALS

CASING - powder painted aluminium; standard colour - white

DIFFUSER - PMMA, tempered glass

REFLECTOR - polished aluminium with a purity of 99,85%

### INSTALLATION

Surface mounted (IP44)

Suspended (IP20)

### ACCESSORIES

	INFO	CODE
Suspension Kit*	1,5m 5x0,75mm	LITH-SUSP

\*Any RAL colour option available



### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

#### EMERGENCY MODULE

3 hr EM

Order code example: **LISM30-4K-DL-WH**