



SOPRANO WM X

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOPRANO WM X 15	14W	1450 Lm	104 lm/W	306 x 28 x 100 mm	SWMX15
SOPRANO WM X 25	25W	2640 Lm	106 lm/W	551 x 28 x 100 mm	SWMX25
SOPRANO WM X 50	48W	5290 Lm	110 lm/W	1091 x 28 x 100 mm	SWMX50
SOPRANO WM X 80	74W	7930 Lm	107 lm/W	1631 x 28 x 100 mm	SWMX80
SOPRANO WM X 110	97W	10570 Lm	109 lm/W	2176 x 28 x 100 mm	SWMX110

*Values are given for colour temperature of 4000K/OPQ diffuser, and may vary for other options

MATERIALS

CASING - powder painted aluminium; standard colour - grey

DIFFUSER - PC

INSTALLATION

Wall mounted

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Opal OPQ

Parabolic Louvers PAR

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL



Order code example: **SWMX15-4K-ST-OPQ-GR**