



## SOLIS LITE

L80 B10 > 55 000h | SDCM 3 | LLMF 78% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOLIS LITE L 40	36W	4320 Lm	120 lm/W	595 x 595 x 12 mm	SLLL40
SOLIS LITE XL 40	36W	4130 Lm	115 lm/W	1195 x 295 x 12 mm	SLXL40

\*Values are given for 4000K colour temperature and may vary for other options

### ACCESSORIES

	INFO	CODE
Surface Mounting Housing*	605 x 605 x 45 mm	SLLL-HOUS
	305 x 1205 x 45 mm	SLXL-HOUS
Plasterboard Ceiling Installation Kit	600 x 600 mm	SOLL-KIT
	300 x 1200 mm	SLXL-KIT
Suspension Y	600 x 600 mm	SLLL-Y
	300 x 1200 mm	SLXL-Y

\*Any RAL colour option available. Order example: **SLLL-HOUS-GR**

### INSTALLATION

Suspended
Surface mounted
Recessed into the modular ceiling
Recessed into plaster-cardboard



### MATERIALS

CASING - electrostatically painted aluminium; standard colour - white

DIFFUSER - PMMA

### ORDER CODE

#### COLOUR TEMPERATURE

3000K	3K
4000K	4K

#### DRIVER TYPE

Standard	ST
Dimming - DALI	DL

#### CASING COLOUR

White	WH
Grey	GR
Black	BL
Custom	RAL

#### EMERGENCY MODULE\*

3 hr	EM
------	----

\*Only available in SLLL40 on request

Order code example: **SLLL40-4K-DL-WH**