



## SOLIS SQ

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOLIS SQ 45 (600 x 600)	38W	4370 Lm	115 lm/W	595 x 595 x 75 mm	SOSQ45
SOLIS SQ 45 SM (Surface Mounted)	38W	4370 Lm	115 lm/W	595 x 595 x 75 mm	SQSM45

\*Values are given for 4000K colour temperature and may vary for other options

### MATERIALS

CASING - electrostatically painted aluminium; standard colour - white

DIFFUSER - PMMA

### INSTALLATION

Surface mounted

Recessed into the modular ceiling

Recessed into plaster-cardboard

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

#### EMERGENCY MODULE\*

3 hr EM

\*Only available in SOSQ45 on request

Order code example: **SOSQ45-4K-DL-WH**

