


LITHIUM SWIVEL

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM SW S 15	15W	1660 Lm	111 lm/W	Ø 135 x 120 mm	118 mm	LISS15
LITHIUM SW S 20	21W	2290 Lm	109 lm/W	Ø 135 x 120 mm		LISS20
LITHIUM SW L 15	15W	1580 Lm	105 lm/W	Ø 160 x 130 mm	144 mm	LISL15
LITHIUM SW L 20	21W	2180 Lm	104 lm/W	Ø 160 x 130 mm		LISL20

*Values are given for 4000K colour temperature and may vary for other options

MATERIALS

CASING - aluminium

DIFFUSER - transparent tempered glass

REFLECTOR - polished and faceted aluminium with a mirror finish

INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

EMERGENCY MODULE

3 hr EM

Order code example: **LISS20-4K-DL**