



IPSILO 2X

L90 > 100 000 h (Ts-85 °C) | CRI > 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
IPSILO 2X 8	160W	25430 Lm	159 lm/W	765 x 260 x 75 mm	IP2X8
IPSILO 2X 10	200W	32428 Lm	162 lm/W	945 x 260 x 75 mm	IP2X10
IPSILO 2X 12	240W	38632 Lm	161 lm/W	1115 x 260 x 75 mm	IP2X12
IPSILO 2X 14	300W	48298 Lm	161 lm/W	1285 x 260 x 75 mm	IP2X14

*Values are given for 60° beam angle and may vary for other options

MATERIALS

CASING - aluminum extrusion, coated.
Mounting bracket - steel

DIFFUSER - tempered glass

INSTALLATION

Surface mounted

Suspended (supply cable 1,00 m /
3 pin connector)

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

BEAM ANGLE

30° 30

60° 60

90° 90

30 x 90° 30x90

EMERGENCY MODULE

3 hr EM

ADD-ONS

Motion Sensor MS



Order code example: **IP2X8-4K-DL-30**