



## RESTO

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
RESTO 35	31W	3410 Lm	110 lm/W	1145 x 126 x 60 mm	REST35
RESTO 40	37W	4240 Lm	115 lm/W	1435 x 126 x 60 mm	REST40

\*Values are given for colour temperature of 4000K / OPQ diffuser, and may vary for other options

### MATERIALS

CASING - powder painted steel sheet body; standard colour - white

DIFFUSER - opal

### INSTALLATION

Surface mounted

Suspended

### FIXINGS

	INFO	CODE
End Cap*	Single**	REST-ENDCAP
Joint*	Linear	REST-JOINT-L
Suspension kit	Simple INOX	ZLISS-INOX
	Simple INOX Y	ZLISS-INOX-Y
	Electrical **	ZLISS-SUSP
	Electrical Y**	ZLISS-SUSP-Y

\*Only for PARS version

\*\*Any RAL colour option available. Order example: **ZLISS-SUSP-GR**



### ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Microprismatic	HEX
Opal	OPQ
Parabolic Louvers Satin	PARS
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE	
3 hr	EM

Order code example: **REST35-4K-ST-OPQ-WH**