



## LITHIUM

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM S 15	15W	1720 Lm	115 lm/W	Ø 155 x 115 mm	136 mm	LIS15
LITHIUM S 25	21W	2370 Lm	113 lm/W	Ø 155 x 115 mm		LIS25
LITHIUM M 15	15W	1760 Lm	117 lm/W	Ø 195 x 120 mm	175 mm	LIM15
LITHIUM M 25	21W	2430 Lm	116 lm/W	Ø 195 x 120 mm		LIM25
LITHIUM M 35	29W	3260 Lm	112 lm/W	Ø 195 x 120 mm		LIM35
LITHIUM L 15	15W	1740 Lm	116 lm/W	Ø 230 x 120 mm	212 mm	LIL15
LITHIUM L 25	21W	2400 Lm	114 lm/W	Ø 230 x 120 mm		LIL25
LITHIUM L 35	29W	3220 Lm	112 lm/W	Ø 230 x 120 mm		LIL35

\*Values are given for 4000K colour temperature and may vary for other options

### MATERIALS

CASING - aluminium

DIFFUSER - transparent tempered glass

REFLECTOR - polished and faceted aluminium with a mirror finish

### INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard



### ORDER CODE

#### COLOUR TEMPERATURE

3000K      3K

4000K      4K

#### DRIVER TYPE

Standard      ST

Dimming - DALI      DL

#### EMERGENCY MODULE

3 hr      EM

Order code example: **LIM35-4K-DL**