

## INDI X WM

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
INDI X WM 20	25W	2390 Lm	96 lm/W	545 x 60 x 75 mm	INXW20
INDI X WM 40	48W	4780 Lm	100 lm/W	1085 x 60 x 75 mm	INXW40
INDI X WM 60	68W	7170 Lm	105 lm/W	1625 x 60 x 75 mm	INXW60
INDI X WM 80	90W	9560 Lm	106 lm/W	2165 x 60 x 75 mm	INXW80

\*Values are given for colour temperature of 4000K and may vary for other options

### MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey



DIFFUSER - PMMA opal

### INSTALLATION

Wall mounted

### FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAP-S
Joints	Inline	INDI-JOINT-I
	Corner 90°*	INDI-JOINT-C



### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

#### EMERGENCY MODULE\*

3 hr EM

\*Only available in INXW60 and INXW80 on request

Order code example: **INXW20-4K-ST-GR**