



# HULK

L90 B10 100 000 h (Ta-25 °C | CRI > 80

| PRODUCT NAME | POWER CONSUMPTION | LUMEN OUTPUT* | EFFICACY* | PRODUCT SIZE      | ORDER REFERENCE |
|--------------|-------------------|---------------|-----------|-------------------|-----------------|
| HULK 160     | 160W              | 22240 Lm      | 139 lm/W  | 420 x 317 x 95 mm | HULK160         |
| HULK 200     | 200W              | 30000 Lm      | 150 lm/W  | 592 x 317 x 95 mm | HULK200         |
| HULK 240     | 240W              | 34320 Lm      | 143 lm/W  | 592 x 317 x 95 mm | HULK240         |
| HULK 300     | 300W              | 44700 Lm      | 149 lm/W  | 765 x 317 x 95 mm | HULK300         |

\*Values are given for 60° beam angle and may vary for other options

## MATERIALS

CASING - aluminum extrusion, coated.  
Mounting bracket - steel

DIFFUSER - tempered glass

## INSTALLATION

Surface mounted

Suspended (includes 5m flex with plug)

## ORDER CODE

### COLOUR TEMPERATURE

3000K      3K

4000K      4K

### DRIVER TYPE

Standard      ST

Dimming - DALI      DL

### BEAM ANGLE

30°      30

60°      60

90°      90

### EMERGENCY MODULE

3 hr      EM

### ADD-ONS

Motion Sensor      MS



Order code example: **HULK160-4K-DL-30**