



SOLIS RM IP65

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOLIS RM IP65 L 50	43W	5100 lm	119 lm/W	595 x 595 x 90 mm	SLIP50
SOLIS RM IP65 XL 50	43W	4910 lm	114 lm/W	1195 x 295 x 90 mm	SXIP50
SOLIS RM IP65 L 115	100W	11470 lm	115 lm/W	595 x 595 x 90 mm	SLIP115
SOLIS RM IP65 XL 100	84W	9820 lm	117 lm/W	1195 x 595 x 90 mm	SLIP100

* Values are given for colour temperature of 4000K / OPQ diffuser, and may vary for other options

MATERIALS

CASING - powder painted steel;
standard colour - white

DIFFUSER - PMMA, tempered glass

INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Microprismatic HEX

Opal OPQ

Parabolic Louvers PAR

Tempered glass GLS

CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM



Order code example: **SLIP50-4K-ST-OPQ-WH-EM**