

## OMICRON CB

L90 B10 > 60 000h | SDCM 3 | LLMF 90% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
OMICRON CB 5	128W	17900 Lm	140 lm/W	610 x 130 x 110 mm	OMCB5
OMICRON CB 6	166W	23160 Lm	140 lm/W	720 x 130 x 110 mm	OMCB6

\*Values are given for 50° beam angle, and may vary for other options

### FIXINGS

	CODE
Single fitting mounting bracket set, for ceiling mounting	OMSN
Double fitting adjustable angle bracket, for mounting two fittings together. Angle adjustment up to 45 deg	OMDB
Adjustable wall bracket set, for wall mounting and angle adjustment	OMWB
Masking frame, for recessed installation	OMMF
Frame with protection grid, Increases the product's resistance to impacts, IK11	OMPF
Suspension kit, 5 m length chains	OMSK

### MATERIALS



CASING - aluminium profile body
DIFFUSER - tempered glass
BRACKET - steel

### INSTALLATION

Surface mounted
Suspended
Wall mounted
Recessed

### ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
5000K	5K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
BEAM ANGLE	
30°	30
50°	50
70°	70



Order code example: **OMCB5-4K-ST-50**