

SOLIS P

L80 B10 > 72 000h | SDCM 3 | LLMF 86% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOLIS P M 15	16W	1330 Lm	83 lm/W	595 x 295 x 80 mm	SOPM15
SOLIS P M 20	24W	2210 Lm	92 lm/W	595 x 295 x 80 mm	SOPM20
SOLIS P L 30	24W	2870 Lm	120 lm/W	595 x 595 x 80 mm	SOPL30
SOLIS P L 50	38W	4750 Lm	125 lm/W	595 x 595 x 80 mm	SOPL50
SOLIS P XL 30	27W	3120 Lm	116 lm/W	1195 x 295 x 80 mm	SPXL30
SOLIS P XL 50	43W	5140 Lm	120 lm/W	1195 x 295 x 80 mm	SPXL50
SOLIS P XXL 60	46W	6070 Lm	132 lm/W	1195 x 595 x 80 mm	SXXL60
SOLIS P XXL 100	76W	9980 Lm	131 lm/W	1195 x 595 x 80 mm	SXXL100

*Values are given for colour temperature of 4000K / HEX diffuser, and may vary for other options

MATERIALS

CASING - powder painted steel; standard colour - white

DIFFUSER - PMMA

INSTALLATION

Recessed into plaster-cardboard ceiling

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Microprismatic HEX

Opal OPQ

CASING COLOUR

White WH



Grey GR

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM



Order code example: **SOPL30-4K-DL-HEX-WH**