



GARDA CR

L70 B10 > 50 000h | SDCM 3 | LLMF 84% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
GARDA CR S 15	11W	1510 Lm	137 lm/W	Ø 155 x 40 mm	GCRS15
GARDA CR S 20	16W	2090 Lm	131 lm/W	Ø 155 x 40 mm	GCRS20
GARDA CR M 25	17W	2460 Lm	145 lm/W	Ø 225 x 40 mm	GCRM25
GARDA CR M 30	22W	3020 Lm	137 lm/W	Ø 225 x 40 mm	GCRM30
GARDA CR M 35	26W	3590 Lm	138 lm/W	Ø 225 x 40 mm	GCRM35

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - powder painted aluminum profile; standard colour - white

DIFFUSER - opal

INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard ceiling

Surface mounted

ACCESSORIES

	INFO	CODE
Surface mounting housing*	Ø 155 x 75 mm	GCRS-SMHO
	Ø 225 x 79 mm	GCRM-SMHO

*Any RAL colour option available. Order example: **GCRS-SMHO-GR**



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE*	
3 hr	EM

*Available in GARDA CR M on request

Order code example: **GCRS20-4K-ST-BL**