



LPM

L90 B10 by 100 000 h (Ts = 25°C) | CRI Ra > 70

| PRODUCT NAME | POWER CONSUMPTION | LUMEN OUTPUT* | EFFICACY* | PRODUCT SIZE | ORDER REFERENCE |
|--------------|-------------------|---------------|-----------|--------------------|-----------------|
| LPM 20 | 20W | 2854 Lm | 143 lm/W | 422 x 260 x 100 mm | LPM20 |
| LPM 30 | 30W | 4842 Lm | 161 lm/W | 422 x 260 x 100 mm | LPM30 |
| LPM 40 | 40W | 6283 Lm | 157 lm/W | 422 x 260 x 100 mm | LPM40 |
| LPM 50 | 50W | 7663 Lm | 153 lm/W | 422 x 260 x 100 mm | LPM50 |
| LPM 60 | 60W | 8908 Lm | 149 lm/W | 422 x 260 x 100 mm | LPM60 |
| LPM 70 | 70W | 9983 Lm | 143 lm/W | 422 x 260 x 100 mm | LPM70 |
| LPM 80 | 80W | 11283 Lm | 141 lm/W | 422 x 260 x 100 mm | LPM80 |
| LPM 90 | 90W | 12314 Lm | 137 lm/W | 422 x 260 x 100 mm | LPM90 |
| LPM 100 | 100W | 13446 Lm | 134 lm/W | 422 x 260 x 100 mm | LPM100 |
| LPM 110 | 110W | 14416 Lm | 131 lm/W | 422 x 260 x 100 mm | LPM110 |
| LPM 120 | 120W | 15276 Lm | 127 lm/W | 422 x 260 x 100 mm | LPM120 |

*Values are given for A9 light distribution/ 4000K colour temperature and may vary for other options

MATERIALS

CASING - cast aluminium, painted
 DIFFUSER - glass, thermally hardened

ORDER CODE

COLOUR TEMPERATURE

| | |
|-------|----|
| 3000K | 3K |
| 4000K | 4K |

DRIVER TYPE

| | |
|----------------------|-----|
| Dimming - DALI | DL |
| Dimming - 1-10V | D10 |
| Dimming - DSI | DSI |
| Dimming - chronoSTEP | DCH |

OPTIC

| |
|------|
| AS6 |
| AS8 |
| AS9 |
| AS14 |



Order code example: **LPM40-4K-DL-AS9**