



IRO Q2

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
IRO Q2 S 50	28W	4915 lm	176 lm/W	616 x 145 x 100 mm	IQ2S50
IRO Q2 S 55	32W	5690 lm	178 lm/W	616 x 145 x 100 mm	IQ2S55
IRO Q2 S 60	31W	5910 lm	191 lm/W	616 x 145 x 100 mm	IQ2S60
IRO Q2 M 85	44W	8600 lm	195 lm/W	1174 x 145 x 100 mm	IQ2M85
IRO Q2 M 100	55W	9830 lm	179 lm/W	1174 x 145 x 100 mm	IQ2M100
IRO Q2 M 120	62W	11815 lm	191 lm/W	1174 x 145 x 100 mm	IQ2M120
IRO Q2 L 105	57W	10370 lm	182 lm/W	1452 x 145 x 100 mm	IQ2L105
IRO Q2 L 145	80W	14220 lm	178 lm/W	1452 x 145 x 100 mm	IQ2L145
IRO Q2 L 150	78W	14765 lm	189 lm/W	1452 x 145 x 100 mm	IQ2L150

* Values are given for 4000K colour temperature and may vary for other options

ACCESSORIES

	INFO	CODE
STAINLESS CLIPS	L-600 - 6x	IROCL6
	L-1200 - 10x	IROCL12
	L-1500 - 12x	IROCL15
PROTECTIVE GRID	700x230x130	IROGR6
	1300x230x130	IROGR12
	1600x230x130	IROGR15
WALL MOUNTING BRACKET 2 set		IRO-WBR

INSTALLATION

Surface mounted

Suspended

MATERIALS

CASING - impact proof polycarbonate

DIFFUSER - UV stabilized polycarbonate

CLIPS - fiber glass reinforced

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

EMERGENCY MODULE

3hr EM

MOTION SENSOR*

Microwave MW

THROUGH WIRING**

5-phase through wiring TW5



*Except IQ2L145

**Available on request

Order code example: **IQ2M100-4K-ST-EM-MW**