



IRO Q1

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
IRO Q1 S 20	12W	2065 lm	172 lm/W	615 x 98 x 84 mm	IQ1S20
IRO Q1 S 30	16W	2825 lm	177 lm/W	615 x 98 x 84 mm	IQ1S30
IRO Q1 S 50	28W	4915 lm	176 lm/W	615 x 98 x 84 mm	IQ1S50
IRO Q1 M 40	24W	4130 lm	172 lm/W	1175 x 98 x 84 mm	IQ1M40
IRO Q1 M 50	27W	5090 lm	189 lm/W	1175 x 98 x 84 mm	IQ1M50
IRO Q1 M 55	33W	5655 lm	171 lm/W	1175 x 98 x 84 mm	IQ1M55
IRO Q1 M 65	37W	6300 lm	170 lm/W	1175 x 98 x 84 mm	IQ1M65
IRO Q1 M 85	46W	8295 lm	180 lm/W	1175 x 98 x 84 mm	IQ1M85
IRO Q1 M 115	65W	11375 lm	175 lm/W	1175 x 98 x 84 mm	IQ1M115
IRO Q1 L 70	40W	7070 lm	177 lm/W	1455 x 98 x 84 mm	IQ1L70
IRO Q1 L 105	57W	10370 lm	182 lm/W	1455 x 98 x 84 mm	IQ1L105
IRO Q1 L 140	82W	14220 lm	173 lm/W	1455 x 98 x 84 mm	IQ1L140

* Values are given for 4000K colour temperature and may vary for other options

ACCESSORIES

	INFO	CODE
STAINLESS CLIPS	L-600 - 6x	IROCL6
	L-1200 - 10x	IROCL12
	L-1500 - 12x	IROCL15
PROTECTIVE GRID	700x230x130	IROGR6
	1300x230x130	IROGR12
	1600x230x130	IROGR15
WALL MOUNTING BRACKET 2 set		IRO-WBR

INSTALLATION

Surface mounted

Suspended

MATERIALS

CASING - impact proof polycarbonate

DIFFUSER - UV stabilized polycarbonate

CLIPS - fiber glass reinforced

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
EMERGENCY MODULE*	
3hr	EM
THROUGH WIRING*	
5-phase through wiring	TW5



*Available in IRO Q1 M and IRO Q1 L on request
Order code example: **IQ1M40-4K-ST-EM**