



LITHIUM MINI SM

L90 B10 > 60 000h | SDCM 3 | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
LITHIUM MINI SM 5	6W	665 Lm	111 lm/W	Ø 82 x 106 mm	LSMM5
LITHIUM MINI SM 10	9W	1085 Lm	121 lm/W	Ø 82 x 106 mm	LSMM10
LITHIUM MINI SM 15	13W	1620 Lm	125 lm/W	Ø 115 x 120 mm	LSMM15
LITHIUM MINI SM 30	26W	2980 Lm	115 lm/W	Ø 115 x 120 mm	LSMM30
LITHIUM MINI SM 20	18W	2240 Lm	124 lm/W	Ø 149 x 143 mm	LSMM20
LITHIUM MINI SM 35	33W	3600 Lm	109 lm/W	Ø 149 x 143 mm	LSMM35
LITHIUM MINI SM 40	40W	3865 Lm	97 lm/W	Ø 149 x 143 mm	LSMM40

*Values are given for colour temperature of 4000K, RBL and may vary for other options

MATERIALS

CASING - powder painted aluminum; standard colour - white

DIFFUSER - transparent structural plastic

REFLECTOR - plastic

INSTALLATION

Surface mounted

Suspended only in Ø 149 mm versions

INFO

Remote emergency pack available

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVERTYPE

Standard ST

Dimming - DALI* DL

REFLECTOR COLOUR

White RWH

Black RBL

Metallic RMT

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

*Available in LSMM15, LSMM25, LSMM30, LSMM35 and LSMM40

Order code example: **LSMM10-4K-DL-RBL-WH**

